


Steckerbelegung I332-USB:



Steckverbinder 1:

PHOENIX, MICRO COMBICON, RM2.5, 12pol.

Pin:	1	+ Endschalter X
	2	+ Endschalter Y
	3	+ Endschalter Z
	4	+ Endschalter U
	5	GND-Extern
	6	- Endschalter X
	7	- Endschalter Y
	8	- Endschalter Z
	9	- Endschalter U
	10	GND-Extern
	11	VCC-Extern
	12	GND-Extern

Steckverbinder 2:

PHOENIX, MICRO COMBICON, RM2.5, 12pol.

Pin:	1	VCC-Extern
	2	GND-Extern
	3	+5V-Intern
	4	Analog-Eingang 1
	5	Analog-Eingang 2
	6	Analog-Eingang 3
	7	Analog-Eingang 4
	8	GND-Intern
	9	Handrad A
	10	Handrad B
	11	Notaus
	12	GND-Extern

Steckverbinder 3:

PHOENIX, MICRO COMBICON, RM2.5, 12pol.

Pin:	1	VCC-IO
	2	GND-IO
	3	Output 1
	4	Output 2
	5	Output 3
	6	Output 4
	7	Output 5
	8	Output 6
	9	Output 7
	10	Output 8
	11	frei
	12	frei

Steckverbinder 4:

PHOENIX, MICRO COMBICON, RM2.5, 12pol.

Pin:	1	Input 1
	2	Input 2
	3	Input 3
	4	Input 4
	5	Input 5
	6	GND-IO
	7	Input 6
	8	Input 13
	9	Input 14
	10	Input 15
	11	Input 16
	12	GND-IO